



SwimPro[™] TOP-MOUNT SAND FILTERS

Offering superb spherical pool filter technology with smooth, efficient flow and balanced backwashing.

SwimPro sand filters feature single piece construction of both main tank body and integral base with corrosion-proof, polymeric material. The internal design features a durable innovative under drain assembly that ensures balanced flow. A versatile seven-position control valve offers both easy operation and maximum efficiency.

For crystal clear, sparkling water with minimum care, SwimPro filters set the standard for performance, value and dependability.

Maximum efficiency, easy operation and dependability



Flange Clamp Design Allows 360° rotation of valve to simplify plumbing.

Corrosion-Proof Tank

Moulded of tough, durable, colourfast polymeric material for dependable, all-weather performance with only minimal care.

Unitised Integrated Base Single piece construction.

SPECIFICATIONS – SwimPro[®] HIGH-RATE SAND FILTERS

| Filter Type | High-Rate Sand ½ Silica Sand (.45 mm55mm), Zeolite or Glass |
|-----------------|---|
| Filter Tank | Moulded Polymeric |
| Underdrain | Full Flow innovative box design for Balanced Flow |
| Control Valve | 40mm 7-Position, Top-Mount Vari-Flo [™] with Lever-Action Handle |
| Valve Fastening | Flange Clamp Design |
| Support Base | Integral with Filter Body |



Patented Full-Flow Design

Innovatively designed under drain assembly for smooth, efficient and balanced full flow.



Vari-Flo[™] 7-Position Control Valve with easy to use lever- action handle lets you "dial" any of seven valve/filter functions.

| PERFORMANCE DATA | | | | | | | | | | |
|------------------|------|-----|---------|---------|------|--------------------|--------|-------|--|--|
| Model No. | Area | LPM | Turn | over | Sand | Dimensions w/Valve | | Valve | | |
| SwimPro | m² | LPM | 4 hours | 8 hours | (kg) | H (mm) | W (mm) | (mm) | | |
| VL210TC | 0.20 | 132 | 31 680 | 63 360 | 68 | 750 | 520 | 40 | | |
| VL240TC | 0.29 | 189 | 45 360 | 90 720 | 91 | 860 | 600 | 40 | | |
| VL270TC | 0.34 | 227 | 54 480 | 108 960 | 136 | 910 | 685 | 40 | | |

To take a closer look at Hayward Filters or other Hayward* products, go to www.hayward-pool.com.au or call 1300 POOLS1

PO Box 4384 | Dandenong South, VIC, 3164







H

SPASA NATIONAL